


ST explosion-protected chain hoist programme _ certified acc. to ATEX





- two speeds as standard
- > Long service life _ in accordance with FEM
- > Maintenance-friendly and cost-effective _ thanks to low-wear brake and slipping clutch



Extremely safe and powerful _

the explosion-protected ST chain hoist



STAHL CraneSystems, market-leader for explosion-protected hoist and crane technology, presents the world's first and only complete Ex chain hoist programme for Zone 1 in accordance with ATEX, and now also for Zone 21 and Zone 22. The approved ST chain hoist programme, ranking among the most outstand-

Application	Category	Protection against	Explosion protection class
Zone 1	II 2 G	Gas	EEx de IIB T4 or EEx de IIC T4
Zone 21	II 2 D	Dust	EEx II 2D 120 °C
Zone 22	II 3 D	Dust	EEx II 3D 120 °C

ing and comprehensive product series at international level, provides the foundation. All components come from a single supplier and from our own production.

- Low headroom ensures that the hook path can be utilised to the full
- Two hoisting speeds and travel speeds as standard
- Powerful, robust hoist motor with consistent running performance and high duty cycle
- Sliding rotor motor with integrated conical disc brake
- The patented safety slipping clutch provides protection against overload and limits the hoisting path
- Single-fall chains (up to 2500 kg) and high-performance motors permit great heights of lift
- Hard-wearing, surface-hardened and galvanised load chain
- Every electric chain hoist is tested with at least 25 % overload
- Customer-specific designs are available fast thanks to the modular system

Version for Zone 22



Version for Zone 1 and Zone 21







Tel: 0411-138 00 Fax: 0411-174 13 E-post: info@pmh.se Hemsida: www.pmh.se