

SH ex wire rope hoist programme _ certified according to ATEX





- > Maintenance-friendly and costsaving _ thanks to low-wear
- > Cost-effective _ excellent cost/ performance ratio
- User-friendly _ ergonomic control pendant with rocker switches



Extremely safe and powerful

the SH explosion-protected wire rope hoist

STAHL CraneSystems is the world market leader for explosion-protected hoists and crane technology. The SH explosion-protected wire rope hoist is specially



designed for working in hazardous areas and meets the ATEX requirements for Zone 1 or Zone 2 or Zones 21 or 22. The basis is the field-proven SH wire rope hoist programme which ranks among the most outstanding and extensive product ranges available internationally. All components come from a single supplier and our own manufacture.

Application	Category	Protection against	Explosion protection class
Zone 1	II 2 G	Gas	Ex de IIB T4 or Ex de IIC T4
Zone 2	II 3 G	Gas	Ex denA IIB T3
Zone 21	II 2 D	Dust	Ex tD A21 IP66 T120°C
Zone 22	II 3 D	Dust	Ex tD A22 IP66 T120°C





- Simple installation on the >de
 principle
- Two hoisting and travel speeds as standard
- Powerful, robust hoist motor with continuous performance and high duty cycle
- Emergency hoist limit switch for top and bottom hook position as standard
- > Gear with lifetime lubrication
- > No open hoist gearing
- Non-sparking versions available as an option
- > Enclosed cast metal rope guide
- Sliding rotor motor with integrated conical disc brake
- Repeatedly adjustable asbestos-free brake ensures long service life
- Maintenance-friendly thanks to brake wear display
- Components approved by UL
- Modular system means customerspecific solutions are available fast

SWH 5 ex ergonomic, two-step control pendant

- Extremely compact and lightweight
- > Simple one-hand operation
- Up to three two-step rocker switches for hoisting, cross and long travel
- Emergency stop as standard





Tel: 0411-138 00 Fax: 0411-174 13 E-post: info@pmh.se Hemsida: www.pmh.se